

DDS PLUS CONCRETE SCREW

Heraklith® | DDS *plus* concrete screws are specifically suited for mounting wood wool panels directly to normal concrete (2000-2600 kg/m³). Comprehensive international fire testing has shown that combining DDS *plus* screws with the Heraklith® Tektalan A2 or the A2 Decorative panel results in excellent performance in fire-resistant applications.

STANDARD VERSION

The concrete screw consists of steel with a corrosion class C3. The screw can therefore be used in an outdoor environment that is not directly exposed to the elements. The screws come standard in the colours white and nature tone (RAL 1015).



ADVANTAGES

- ✓ Plastic screw head with wood fibre structure for decorative finish
- Simple installation: pre-drill and screw in
- Minimal anchorage depth
- Can be used for fire-resistant applications
- Available in various RAL colours upon request

SPECIFICATIONS

| Art. No. Nature tone | Art. No. White | Screw length (mm) | Panel thickness to (mm) | Units / pack |
|----------------------|----------------|-------------------|-------------------------|--------------|
| 416 810 | 596 858 | 50 | 25 | 100 |
| 416 812 | 416 798 | 75 | 35/50 | 100 |
| 416 813 | 416 802 | 85 | 60 | 100 |
| 416 814 | 416 803 | 100 | 75 | 100 |
| 596 896 | 596 895 | 110 | 85 | 100 |
| 416 815 | 416 804 | 125 | 100 | 100 |
| 416 816 | 416 805 | 150 | 125 | 100 |
| 416 817 | 416 806 | 175 | 150 | 100 |
| 416 818 | 416 807 | 200 | 175 | 100 |
| 416 819 | 416 808 | 225 | 200 | 100 |
| 416 820 | 416 809 | 250 | 225 | 100 |

Different colours upon request




Always process our Heraklith wood wool panels according to our processing instructions. These can be found on heraklith.com/downloads



TECHNICAL INFORMATION

| Corrosion category | C3 | |
|----------------------------------|----------------------------|--|
| Tensile strength concrete C20/25 | 0.5 kN | |
| Screw diameter | 7.5 mm | |
| Head diameter | 26 mm | |
| Drilled hole diameter | 6 mm | |
| Drilled hole depth | 30 mm | |
| Anchoring depth in concrete | 25 mm | |
| Screw drive | Torx T30 | |
| Recommended anchoring material | Concrete (2000–2600 kg/m³) | |



Do you want more information? Please contact us

Knauf Insulation B.V.

Dakota 7 5126 RL Gilze

Tel: + 31 (0)162 - 42 12 45

e-mail: woodwool.export @knaufinsulation.com

www.heraklith.com

Our general sales and delivery conditions apply to all our offers, communications and agreements, notwithstanding any provision to the contrary that can be found on our order forms or elsewhere. An overview of our general terms and conditions can be found on: heraklith.com/downloads. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof.

